## **GENERAL NOTES:**

- 1. These notes are for Standard Drawing E 610-DRIV-12, -13, -15, -16.
- 2. The class VI and VII drives are designed to accommodate a WB-65 (IDV) design vehicle with a 45 ft turning radius.
- (7) The maximum algebraic difference in grades shall not exceed 8% for crasted grade nor 12% for saged grades.
- (8) The minimum driveway pavement section has been designed for 200 trucks per day. If the truck traffic count is greater than 200 per day, the required pavement section shall be as shown elsewhere on the plans.
- $oxed{(9)}$  Driveway embankment slopes within the clear zone for a road functionally classified as follows shall be :
  - 6:1 for an arterial or a high speed (over 40 mph design speed) collector.
  - 4:1 for a local road or a low speed (40 mph or lower design speed) collector.
- (0) Driveway culverts which cannot be located outside the clear zone shall have appropriate end sections at both ends.
- (11) Hc earth cover over culvert or pipe shall be 1 ft or greater.
- (12) Curb ramp type G, as shown on Standard Drawing E 604-SWCR-09, shall be used when sidewalk is adjacent to curb.
- (13) When X is equal to or greater than 2 ft but less than 5 ft, curb ramp type H as shown on Standard Drawing E 604-SWCR-09 shall be used.
- (14) When X is equal to or greater than 5 ft, no curb ramp is required.

## LEGEND

(3) Longitudinal joint

(4) Keyway joint

5) ½ in. preformed joint filler

(6) Monolithic curb

(F) Concrete sidewalk

S For type and thicknes equivalent to surface in place, see plans.

(U) Concrete curb ramp

X = Distance between face of curb and sidewalk

W = Width of sidewalk

\_\_\_\_\_\_ Cement Concrete Pavement for Driveways

|||||| Curb ramp

Curb ramp view

INDIANA DEPARTMENT OF TRANSPORTATION

CLASS VI AND VII DRIVES GENERAL NOTES AND LEGEND

MARCH 2002

STANDARD DRAWING NO. E 610-DRIV-14



/s/Richard L. VanCleave 3-01-02 DESIGN STANDARDS ENGINEER DATE

/s/ Richard K. Smutzer 3-01-02
CHIEF HIGHWAY ENGINEER DATE

ESIGN STANDARDS ENGINEER